

Product Catalog



SHENZHEN ZHIXING YUANFANG TECHNOLOGY CO., LTD.



Model:JYX

DIMENSIONS	RANGE
1900*720*1370mm	160km@35Km/h
WHEELBASE	TOP SPEED
1350mm	80Km/h
WEIGHT	BATTERY
88kg(excluding battery)	Li-ion 72V45Ah (87.6V Max)
TIRES	FAST CHARGING
F: 120/70-13 R: 120/70-12	OBC 3.3KW
BRAKES	MOTOR
F:Disc R:Disc	4000W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	1.3 hours (100%) 25 minutes (80%)
INPUT VOLTAGE	
110V/220V (AC)	



Model:APQ-4000

DIMENSIONS	RANGE
1960*730*1150mm	120km@45Km/h
WHEELBASE	TOP SPEED
1395mm	85Km/h
WEIGHT	BATTERY
115kg(excluding battery)	Li-ion 72V50Ah (87.6V Max)
TIRES	FAST CHARGING
F: 90/90-12 R: 90/90-12	OBC 3.3KW
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	1.3 hours (100%) 25 minutes (80%)
INPUT VOLTAGE	
110V/220V (AC)	



Model:U2-2000

DIMENSIONS	INPUT VOLTAGE
1800*800*1050mm	110V/220V (AC)
WHEELBASE	RANGE
1290mm	75km@35Km/h
WEIGHT	TOP SPEED
66kg(excluding battery)	51Km/h
TIRES	BATTERY
F: 90/90-12 R: 90/90-12	Li-ion 72V30Ah (87.6V Max)
BRAKES	MOTOR
F:Disc R:Disc	2000W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	6 hours(Customizable)



Model:BOX-3000

DIMENSIONS	INPUT VOLTAGE
2160*780*1130mm	110V/220V (AC)
WHEELBASE	RANGE
1390mm	150km@40Km/h
WEIGHT	TOP SPEED
108kg(excluding battery)	100Km/h
TIRES	BATTERY
F: 3.0-17 R: 100/90-17	Li-ion 72V67Ah (87.6V Max)
BRAKES	MOTOR
F:Disc R:Disc	4500W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	7 hours(Customizable)



Model:HG2-2000

DIMENSIONS	INPUT VOLTAGE
1905*680*1140mm	110V/220V (AC)
WHEELBASE	RANGE
1340mm	80km@35Km/h
WEIGHT	TOP SPEED
105kg(excluding battery)	65Km/h
TIRES	BATTERY
F: 110/70-12 R: 110/70-12	Li-ion 72V32Ah (87.6V Max)
BRAKES	MOTOR
F:Disc R:Disc	2000W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	6 hours(Customizable)



Model:HG2-2000

DIMENSIONS	INPUT VOLTAGE
1905*680*1140mm	110V/220V (AC)
WHEELBASE	RANGE
1340mm	100km@35Km/h
WEIGHT	TOP SPEED
105kg(excluding battery)	70Km/h
TIRES	BATTERY
F: 110/70-12 R: 110/70-12	Li-ion 72V32Ah (Optional dual batteries)
BRAKES	MOTOR
F:Disc R:Disc	2500W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours



Model:PM-2000

DIMENSIONS	INPUT VOLTAGE
1840*720*1140mm	110V/220V (AC)
WHEELBASE	RANGE
1350mm	55km@35Km/h
WEIGHT	TOP SPEED
73kg(excluding battery)	53Km/h
TIRES	BATTERY
F: 90/90-12 R: 90/90-10	Pb-A 72V20Ah(84V Max)
BRAKES	MOTOR
F:Disc R:Disc	2000W
SUPSPENSION	CHARGING TIME
F/R: Hydraulic	7 hours(Customizable)



Model:JCH2-4000

DIMENSIONS	RANGE
1950*715*1430mm	120km@45Km/h
WHEELBASE	TOP SPEED
1400mm	85Km/h
WEIGHT	BATTERY
89kg(excluding battery)	Li-ion 72V50Ah (87.6V Max)
TIRES	FAST CHARGING
F: 110/70-12 R: 110/70-12	OBC 3.3KW
BRAKES	MOTOR
F:Disc R:Disc	4000W
SUPSPENSION	CHARGING TIME
F/R:Hydraulic	1.3 hours (100%) 25 minutes (80%)
INPUT VOLTAGE	
110V/220V (AC)	



Model:XT-3000

DIMENSIONS	INPUT VOLTAGE
2250*715*1460mm	110V/220V (AC)
WHEELBASE	RANGE
1460mm	140km@40Km/h
WEIGHT	TOP SPEED
125kg(excluding battery)	90Km/h
TIRES	BATTERY
F: 90/90-17 R: 110/80-17	Li-ion 72V50Ah(87.6V Max)
BRAKES	MOTOR
F:Disc R:Disc	4500W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:DU-3000

DIMENSIONS	INPUT VOLTAGE
2050*815*1350mm	110V/220V (AC)
WHEELBASE	RANGE
1390mm	100km@35Km/h
WEIGHT	TOP SPEED
122kg(excluding battery)	95Km/h
TIRES	BATTERY
F: 110/70-17 R: 140/70-17	Li-ion 72V50Ah
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours



Model:BD-2-1200

DIMENSIONS	INPUT VOLTAGE
1800*710*1150mm (1325 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1255mm	75km@35Km/h
WEIGHT	TOP SPEED
62kg(excluding battery)	55Km/h
TIRES	BATTERY
F: 3.00-10 R: 3.00-10	Li-ion 72V20Ah
BRAKES	MOTOR
F:Disc R:Disc	1200W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:DH-3000

DIMENSIONS	INPUT VOLTAGE
1950*675*1135mm (1275 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1340mm	100km@35Km/h
WEIGHT	TOP SPEED
84kg(excluding battery)	70Km/h
TIRES	BATTERY
F: 90/90-14 R: 90/90-14	Li-ion 72V35Ah
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:N9

DIMENSIONS	INPUT VOLTAGE
1900*690*1200mm (excluding mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1320mm	65km@35Km/h
WEIGHT	TOP SPEED
95kg(excluding battery)	50Km/h
TIRES	BATTERY
F: 70/90-10 R: 70/90-10	Li-ion 72V30Ah
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
Hydraulic	5 hours(Customizable)



Model:N9

DIMENSIONS	INPUT VOLTAGE
1900*690*1200mm (excluding mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1320mm	100km@25Km/h
WEIGHT	TOP SPEED
91kg(excluding battery)	70Km/h
TIRES	BATTERY
F: 70/90-10 R: 70/90-10	Li-ion 72V32Ah
BRAKES	MOTOR
F:Disc R:Disc	2000W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:V11-3000

DIMENSIONS	INPUT VOLTAGE
1930*675*1100mm (1325 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1340mm	100km@25Km/h
WEIGHT	TOP SPEED
82kg(excluding battery)	75Km/h
TIRES	BATTERY
F: 80/90-14 R: 90/90-14	Li-ion 72V32Ah
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:V11-3000

DIMENSIONS	INPUT VOLTAGE
1930*675*1100mm	110V/220V (AC)
WHEELBASE	RANGE
1340mm	80km@35Km/h
WEIGHT	TOP SPEED
82kg(excluding battery)	80Km/h
TIRES	BATTERY
F: 80/90-14 R: 90/90-14	Li-ion 72V32Ah(87.6V Max)
BRAKES	MOTOR
F:Disc R:Disc	3000W
SUPSPENSION	CHARGING TIME
F/R: Hydraulic	5 hours(Customizable)



Model: YTZM-1000

DIMENSIONS	INPUT VOLTAGE
1960*710*1140mm (1325 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1400mm	100km@25Km/h
WEIGHT	TOP SPEED
80.5kg(excluding battery)	55Km/h
TIRES	BATTERY
F: 90/90-12 R: 90/90-12	Li-ion 72V32Ah
BRAKES	MOTOR
F:Disc R:Disc	1500W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:MLDN-1000

DIMENSIONS	INPUT VOLTAGE
1920*710*1100mm (1325 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1320mm	100km@25Km/h
WEIGHT	TOP SPEED
82kg(excluding battery)	55Km/h
TIRES	BATTERY
F: 90/90-10 R: 90/90-10	Li-ion 72V32Ah
BRAKES	MOTOR
F:Disc R:Disc	1500W
SUPSPENSION	CHARGING TIME
Hydraulic	6 hours(Customizable)



Model:XQL-350

DIMENSIONS	INPUT VOLTAGE
1455*620*1070mm (1325 with mirrors)	110V/220V (AC)
WHEELBASE	RANGE
1115mm	80km@25Km/h
WEIGHT	TOP SPEED
37kg(excluding battery)	33Km/h
TIRES	BATTERY
F: 60/90-10 R: 60/90-10	Li-ion 48/60V20Ah
BRAKES	MOTOR
F:Drum R:Drum	500W
SUPSPENSION	CHARGING TIME
Hydraulic	5 hours(Customizable)



Model:CH-2000(Delivery)

DIMENSIONS	INPUT VOLTAGE
1910*760*1140mm	110V/220V (AC)
WHEELBASE	RANGE
1390mm	105km@35Km/h
WEIGHT	TOP SPEED
66kg(excluding battery)	65Km/h
TIRES	BATTERY
F: 80/90-12 R: 80/90-12	Li-ion 60V50Ah
BRAKES	MOTOR
F:Disc R:Disc	2000W
SUPSPENSION	CHARGING TIME
Hydraulic	8 hours(Customizable)



Model:CH-2000

DIMENSIONS	INPUT VOLTAGE
1910*720*1080mm	110V/220V (AC)
WHEELBASE	RANGE
1390mm	105km@35Km/h
WEIGHT	TOP SPEED
63kg(excluding battery)	60Km/h
TIRES	BATTERY
F: 80/90-12 R: 80/90-12	Li-ion 60V50Ah
BRAKES	MOTOR
F:Disc R:Disc	1500W
SUPSPENSION	CHARGING TIME
Hydraulic	8 hours(Customizable)



Model:V3-300

DIMENSIONS	INPUT VOLTAGE
1420*635*910mm	110V/220V (AC)
WHEELBASE	RANGE
985mm	20km@25Km/h
WEIGHT	TOP SPEED
39kg(excluding battery)	30Km/h
TIRES	BATTERY
F: 3.00-10 R: 3.00-10	Pb-A 36V12Ah(40.5V Max)
BRAKES	MOTOR
F:Disc R:Disc	300W
SUPSPENSION	CHARGING TIME
F/R: Hydraulic	6 hours(Customizable)



Model:M600

DIMENSIONS	MAXIMUM TORQUE OF THE DRIVING
1060*570*670mm	35N/m
WHEELBASE	MAX SPEED
700mm	25Km/h
WEIGHT	ENDURANCE
22kg(excluding battery)	30Km
FORK TRAVEL	BATTERY
60mm	36V5.2Ah
MINIMUM GROUND CLEARANCE	MAXIMUM OUTPUT POWER
200mm	600W
BACK REDUCTION/WHEEL TRAVEL	CHARGING TIME
18mm	2.5 hours(Customizable)



Model:Dirt Bike

F/R SUSPENSION	INPUT VOLTAGE
F: Inverted Suspension Fork R: Shock Absorber	110V/220V (AC)
FRAME	RANGE
6061 Forged Aluminum	60-70km
WATER RESISTANCE	TOP SPEED
IP65	85Km/h
TIRES	BATTERY
F/R: 70/100-19	Li-ion 21700 (Removable)
BRAKES	QS MID-MOTOR
F:Disc R:Disc	Rated:4KW 10.2NM Peak:8KW 39NM Belt + 420 Drive Chain
MAX CLIMBING ANGLE	CHARGING TIME
45°	3-4 hours



Model:UTV-550

DIMENSIONS	RANGE
2340x1430x1830mm	100km
WHEELBASE	TOP SPEED
1760mm	50Km/h
WEIGHT	BATTERY
350kg	LFP 72V200Ah
TIRES	FAST CHARGING
F: 21x7-10 R: 22x10-10	OBC 3.3KW
BRAKES	MOTOR
F:Disc R:Disc	10KW
CHARGING TIME	SUPSPENSION
6 hours	F: Dual A arms independent supspension R: Swing arm Dual Shocks
INPUT VOLTAGE	
110V/220V (AC)	



Model:Golf Cart

DIMENSIONS	INPUT VOLTAGE
2980*1250*1980mm	110V/220V (AC)
WHEELBASE	RANGE
1700mm	110km
WEIGHT	TOP SPEED
505kg	40Km/h
TIRES	BATTERY
F/R: 23/10.5 - 14	LFP 48V105Ah
BRAKES	MOTOR
F:Disc R:Disc	5KW
SUPSPENSION	CHARGING TIME
F:McPherson Suspension R:Integrated Rear Axle- Hydraulic Shock Absorber	6 hours